Thank you for purchasing an Outdoor Revolution product, this product will give years of satisfactory service if basic instructions are followed; our products are designed for durability and ease of erection.



<u>www.outdoor-revolution.com</u> Unit 1 Brick Park Bretfield Court Bretton Street Industrial Estate Dewsbury West Yorkshire WF12 9BY











IMPORTANT: PLEASE CHECK YOUR EQUIPMENT

1 x 68HD Flysheet (or outer)


1 x Single Inflation Point Oxygen Air-Frame

- **1 X DUAL ACTION HAND PUMP**
 - 1 x BAG OF PEGS
 - 1 x Repair Kit
 - 1 x Holdall
 - GUYLINES

LUMI-LITE HANGING POINTS

ENDURANCE STORM STRAPS

Cayman Cacos Uno Height : 215cm Adjustable Height: 180-240CM





We highly recommend that you insure your driveaway against storm damage or accidental damage, as the warranty does not cover such eventualities. The manufacturer <u>IS NOT</u> liable for any damage caused to the awning or its contents due to misuse, incorrect pitching or extreme weather (full warranty details on rear of booklet).

THE WARRANTY (CONTINUED ...)

- Flaws in the fabric caused by excessive use
- Imperfections and pulls in mesh doors due to wear and tear
- Water ingress through fabric as a result of UV degradation
- Water ingress through seams caused by excessive abrasion of seams or taped seam
- Broken zips caused by over tensioning, forcing or snagging
- Over tensioned/stretched seams coming apart
- Buckles subjected to undue force or abrasion
- Lost/popped out eyelets
- Broken holdalls
- Pole breakages or tube punctures (where applicable)
- Collateral damage from a pole breakage
- UV degradation
- Condensation, (a natural occurrence, exacerbated by insufficient ventilation opening)
- Consequential damage/loss to property/belongings (either inside or outside of the product) or shortening of holidays

'Outdoor Revolution' work very closely with our retail partners to manage all warranty repairs/issues:

**Please contact your retailer immediately, (even if purchased online) if you feel your 'Outdoor Revolution' product has a genuine warranty issue. The retailer, in turn, will raise the issue with ourselves and we will action with the retailer, according to the nature of the claim.

**Please ensure the product is clean and dry and as close to its original condition as possible, before sending back for checking.

**Wet or dirty products will not be accepted back for checking/warranty claims.

** It is important to note that the sales contract between yourself and the retailer you purchased the 'Outdoor Revolution' product from, remains valid throughout any warranty claim and your statutory rights are not affected.

OUTDOOR REVOLUTION GUARANTEE

'Outdoor Revolution' products are designed and produced to the highest possible manufacturing standards. The best quality fabrics and components available are used for each specific item and a rigorous checking process of finished products is in place.

All finished products are:

- Checked for and are free of minor defects
- Are fit for the purpose/use that they are intended
- Are of a satisfactory quality

It is important that correct care is taken when opening the product, erecting, using and just as importantly, packing away the product. Following these rules will keep your product in reliable working condition for many years. Failure to adhere to these simple guidelines may cause unnecessary damage to the product (see formal instructions for hints and tips on handling/erecting the product). A repair kit is included in the product to help resolve any minor issues.

THE WARRANTY

The 'Outdoor Revolution' warranty lasts for 12 months from the original date of purchase (please keep all receipts or copies of any relevant transaction to substantiate the purchase date). The warranty only covers workmanship and fabric/ components. Any faults found within 6 months of purchase will be investigated by 'Outdoor Revolution'. Faults found outside of the initial six months of purchase will need to be proven by you, the purchaser, in line with current consumer legislation after the short-term right to reject has ended.

Retailer will not refund a purchase if no fault is found.

Product warranty **must** be registered **BEFORE** use, via: <u>www.outdoor-</u> <u>revolution.com</u>, and as soon as possible from the date of purchase.

The manufacturer's warranty does not cover the following:-

- General wear and tear over extended periods of use or seasonal pitching of the product
- Accidental damage caused by but not exclusive to, humans, animals or weather

IMPORTANT INFORMATION

- Please do not leave for your holiday without fully erecting and checking you have all the contents for your awning; if you're missing anything, please contact your retailer immediately before use.
- Please also note that man-made fabrics are prone to condensation when the warm air and moisture inside the awning comes into contact with the colder air on the outside of the awning fabric. This is a perfectly natural occurrence and should not be confused with leaking. Ensure all ventilation points are open whenever possible to help combat condensation.
- Ideally, erect your awning for some period before use allowing it to weather. 'Weathering' can take a few uses of the awning before it becomes fully effective. Seam sealant can be used to solve any persistent weeps; this process is completely normal. 'Weathering' is the process of allowing your canvas product get wet, then dry approximately two to three times in order to strengthen and further waterproof the seams and stitching on the fabric.
- Make sure that before erecting, you site the awning on clear level ground, with no sharp objects underneath and zips fully closed. (We recommend laying a groundsheet down to keep the awning dry and clean).
- We suggest conducting a trial run of your awning to familiarise yourself with the set up and use of the awning. If you have any issues relating to pitching your awning, please contact your dealer for assistance before going on holiday.
- Please note this awning is designed for 'touring' and not for permanent pitch.
- After use, always dry and air the awning before packing away to prevent mildew or mould.
- Any dirt or stains can be removed by brushing or gently washing with warm water. DO NOT use detergents, as this will destroy the waterproofing on the fabrics.
- DO NOT cook or smoke in this awning; although the outer fabric is flame retardant treated, it will still melt.
- In the event of damage; please contact your retailer. If for whatever reason you are unable to contact them, please email: <u>cs@blue-diamond-</u> <u>products.co.uk</u> and our customer service team will be happy to help!

OPTIONAL ACCESSORIES

- <u>Stone Protection Footprint</u> Groundsheet to give additional protection to your awning.
- <u>Two-Berth Inner-Tent -</u> Clip-in micro-polyester inner tent, suitable for sleeping two adults or a double air-bed.
- Jet Stream Electric Pump A high-pressure internal 12V electric airpump, designed for quick, effortless inflation.
- <u>Magnetic Drive Away Strip</u> The newest technology for attaching driveaway awnings to magnetic vehicles!
- <u>Lumi-Link Tube Light Kit</u> A connecting 12V LED tube light system, helping to maintain good lighting within the awning.

 \Rightarrow Available selection of foldaway chairs, furniture and sleeping bags.

⇒ Visit: <u>www.outdoor-revolution.com</u> for more information on the optional extras.

LIFETIME GUARANTEE

The air-frame tubes incorporate an exclusive "LIFETIME GUARANTEE".

You must register for the "LIFETIME GUARANTEE" on the 'Outdoor Revolution' website within 14 days to validate it.

Terms and Conditions apply - find the full terms and conditions on our website!

TROUBLE SHOOTING

<u>PROBLEM</u>	<u>REASON</u>	SOLUTION
The air-tube keeps deflating after removing the pump.	The 'Dynamic Speed Valve' button hasn't been pressed back out.	Press the quick release button back out to shut the valve.
The awning is leaking.	The awning requires weathering two or three times before it fully seals itself, so you may experience a little bit of weeping. This could also be condensation, an inevitable occurrence.	Allow the awning to get wet, then dry two to three times. Open all of the ventilation points to increase air flow and reduce condensation.
Bowing and twisting of the tubes.	The tubes can twist inside the sleeves, particularly when packing away, so next time the tube bows	Un-zip the sleeve whilst the tube is deflated and re- position the tube.

IN THE EVENT OF A PUNCTURE

If you have a small puncture in your air-frame tube, you can easily repair it using the standard puncture repair kit.

- To remove the air-frame tube deflate the tube and then unzip the two protective sleeves over the tube and pull the air-tube out. Do not un-zip the sleeves whilst the tube is inflated.
- Locate and repair the puncture on the air-frame bladder.
- Place the air-tube back into the sleeves in the correct place, with the valves in the valve hole. Ensure the tube is straight and not twisted.
- Zip the two sleeves back up fully.
- Inflate the air-frame tube again, ensuring that the puncture has now been repaired.
- If this process doesn't work you may have to buy a new bladder.
- **Spare air-frame bladders can be purchased to replace damaged ones. Visit the spares section at: <u>www.outdoor-revolution.com</u>, or contact us on: 01924 455313**

Awnings will not be replaced because of damaged bladders

PACKING AWAY YOUR AWNING

- Remove the cowl from the vehicle. Zip-up all of the windows and doors before unpegging.
- Unpeg the guylines, storm straps and most of the pegs around the awning, leaving the four corners pegged out.
- Remove the pins from the bottom of the poles and push the poles out of the sleeves in the awning.
- Unpeg the four corners.
- Lay the awning flat on the ground.



2. Measure the width of the bag up against the width of the folded awning, to make sure the awning is going to fit.



4. Place the rolled awning on to the bag and pull the sides up round it. Finally, zip-up the bag.

1. Fold the awning lengthways to

make a long, thin sausage shape.

3. Begin to roll the awning as tight as possible.



PLEASE READ THE INSTRUCTIONS CAREFULLY

 $\underline{\text{TIP:}}$ Refer to the photographs to help when pitching your 'Movelite Cayman Cacos Uno'.

1. Spread the flysheet out on the ground next to your vehicle, with the cowl side laying parallel to it.




3. Locate the first of three 'Dynamic Speed Valves' and ensure the valve is **closed,** before attaching the pump (the valve is closed when the button is pressed out).



5. Replace the cap on the 'Dynamic Speed Valve' and cover the valves with the flap to prevent water getting inside.



2. Peg down the four corners of the flysheet to keep the awning in place whilst you erect the poles.





4. Next, attach the pump end to the valve by twisting it into place and begin to inflate until you can give it a good squeeze.



6. Start at one side of the awning and work your way around, pegging down all of the adjustable pegging points to secure the awning.



8. Take the awning piping and slide it through the awning channel, until the awning is in the desired position on the vehicle. We recommend using a 'Drive Away Kit', as it will make this process much easier.




7. Additionally, peg out all of the guylines on the awning to apply additional stability; adjust the guylines to

make them tighter.



9. Peg the bottom of the cowl down using the adjustable pegging points, to prevent this from flapping. *Note: Threading the cowl on and off the vehicle can be quite a difficult task, once the awning is in position. We recommend using a 'Drive Away Kit', which makes it much easier to attach. The images below demonstrate this:





There is a video on the 'Hints and Tips' section of the "Outdoor Revolution" website, explaining how to use a 'Drive Away Kit': **www.outdoorrevolution.com**.

Note: Alternatively, there is a 'Magnetic Drive Away Strip', which can be used with smaller, magnetic vehicles. The image below demonstrates this:



WARNING: Never un-zip the zips on the protective sleeves whilst the air-frame tubes are inflated; this will result in the tube bursting or ballooning out of the sleeve, causing damage to the tube and the sleeve. This is not covered under the warranty!