

Thank you for purchasing an "Outdoor Revolution" product, this product will give years of satisfactory service if basic instructions are followed; our products are designed for durability and for ease of erection.



WWW.OUTDOOR-REVOLUTION.COM

UNIT 1 BRICK PARK
BRETFIELD COURT
BRETTON STREET INDUSTRIAL ESTATE
DEWSBURY
WEST YORKSHIRE
WF12 9BY



ESPRIT 360 PRO

INSTRUCTIONS & CARE MANUAL



IMPORTANT: PLEASE CHECK YOUR EQUIPMENT

1 X PATTERNED 800HD FLYSHEET (OR OUTER)

1 X SINGLE INFLATION POINT AIR-FRAME

2 X ROOF SUPPORT AIR-TUBES

1 X BAG OF PEGS

1 X DUAL ACTION HAND PUMP

1 X DRAUGHT SKIRT

1 X REPAIR KIT

1 X HOLDALL

1 X TWIN PIPING (4MM X 6MM)

ENDURANCE STORM STRAPS

GUYLINES


LUMI-LITE & LUMI-LINK HANGING POINTS



ESPRIT 360

Front Height: 180CM

Rear Height: 235CM



We highly recommend that you insure your awning against storm damage or accidental damage, as the warranty does not cover such eventualities. The manufacturer **IS NOT** liable for any damage caused to the awning or its contents due to misuse, incorrect pitching or extreme weather (full warranty details on rear of booklet).

THE WARRANTY (CONTINUED...)

- Accidental damage caused by but not exclusive to, human, animal or weather.
- Flaws in the fabric caused by excessive use.
- Water ingress through fabric as a result of UV degradation.
- Water ingress through seams caused by excessive abrasion of seams or taped seam.
- Broken zips caused by over tensioning, forcing or snagging.
- Over tensioned/stretched seams coming apart.
- Buckles subjected to undue force or abrasion.
- Lost/popped out eyelets.
- Broken holdalls.
- Pole breakages or tube punctures (where applicable).
- Collateral damage from a pole breakage.
- UV degradation.
- Condensation, (a natural occurrence, exacerbated by insufficient ventilation opening).
- Consequential damage/loss to property/belongings (either inside or outside of the product) or shortening of holidays.

'Outdoor Revolution' work very closely with our retail partners to manage all warranty repairs/issues:

**Please contact your retailer immediately (even if purchased online) if you feel your 'Outdoor Revolution' product has a genuine warranty issue. The retailer, in turn will raise the issue with ourselves and we will action; with the retailer, according to the nature of the claim.

**Please ensure the product is clean, dry and as close to its original condition as possible, before sending back for checking.

**Wet or dirty products will not be accepted back for checking/warranty claims.

** It is important to note that the sales contract between yourself and the retailer you purchased the 'Outdoor Revolution' product from, remains valid throughout any warranty claim and your statutory rights are not affected.

OUTDOOR REVOLUTION GUARANTEE

'Outdoor Revolution' products are designed and produced to the highest manufacturing standards. The best quality fabrics and components available are utilised for each specific item and a rigorous checking process of finished products is in place.

All finished products are:-

- Checked for and are free of minor defects
- Are fit for the purpose/use that they are intended
- Are of a satisfactory quality

It is important that correct care is taken when opening the product, erecting, using and just as importantly, packing away the product. Following these rules will keep your product in reliable working condition for many years. Failure to adhere to these simple guidelines may cause unnecessary damage to the product (see formal instructions for hints and tips on handling/erecting the product). A repair kit is included in the product to help resolve any minor issues.

THE WARRANTY

The 'Outdoor Revolution Warranty' lasts for 12 months from the original date of purchase (please keep all receipts or copies of any relevant transaction to substantiate the purchase date). The warranty only covers workmanship and fabric/components. Any faults found within 6 months of purchase will be investigated by Outdoor Revolution. Faults found outside of the initial six months of purchase will need to be proven by you the purchaser, in line with current consumer legislation after the short term right to reject has ended.

Retailer will not refund a purchase if no fault is found.

Product warranty must be registered **BEFORE** use via: www.outdoor-revolution.com and as soon as possible from the date of purchase.

The manufacturer's warranty does not cover the following:-

- General wear and tear over extended periods of use or seasonal pitching of the product
- Accidental damage caused by but not exclusive to, humans, animals or weather

IMPORTANT INFORMATION

- ◆ Please do not leave for your holiday without fully erecting and checking you have all the contents for your awning; if you're missing anything, please contact your retailer immediately before use.
- ◆ Please also note that man-made fabrics are prone to condensation when the warm air and moisture inside the awning comes into contact with the colder air on the outside of the awning fabric. This is a perfectly natural occurrence and should not be confused with leaking. Ensure all ventilation points are open whenever possible to help combat condensation.
- ◆ Ideally, erect your awning for some period before use - allowing it to weather. 'Weathering' can take a few uses of the awning before it becomes fully effective. Seam sealant can be used to solve any persistent weeps; this process is completely normal. 'Weathering' is the process of allowing your canvas product get wet, then dry approximately two to three times in order to strengthen and further waterproof the seams and stitching on the fabric.
- ◆ Make sure that before erecting, you site the awning on clear level ground, with no sharp objects underneath and zips fully closed. (We recommend laying a groundsheet down to keep the awning dry and clean).
- ◆ We suggest conducting a trial run of your awning to familiarise yourself with the set up and use of the awning. If you have any issues relating to pitching your awning, please contact your dealer for assistance before going on holiday.
- ◆ Please note this awning is designed for 'touring' and not for permanent pitch.
- ◆ After use, always dry and air the awning before packing away to prevent mildew or mould.
- ◆ Any dirt or stains can be removed by brushing or gently washing with warm water. DO NOT use detergents, as this will destroy the waterproofing on the fabrics.
- ◆ DO NOT cook or smoke in this awning; although the outer fabric is flame retardant treated, it will still melt.
- ◆ In the event of damage; please contact your retailer. If for whatever reason you are unable to contact them, please email: cs@blue-diamond-products.co.uk and our customer service team will be happy to help!

OPTIONAL ACCESSORIES

- ◆ Treadlite 360—A breathable, cut to size, machine washable carpet for your awnings' living area.
- ◆ Pro Conservatory Annexe - An air-framed annexe that can be zipped onto either side of the awning, offering a sleeping /storage area for up to two adults; even incorporating windows, curtains and convenient access doors.
- ◆ Air Pod Inner Tent—A free-standing two-berth inner-tent, complete with a single inflation point cross-beam air frame.
- ◆ Two-Berth Inner Tent—A micro-polyester inner tent, designed to comfortably sleep two adults.
- ◆ Rear Pad Poles—To ensure a snug fit of your awning to the caravan.
- ◆ Jet Stream Electric Pump/Twin—An internal 12V high-pressure air-pump for effortless inflation of the air-frame.
- ◆ Deluxe Tech Storm Kit— A handy kit containing a single 'Curved Mallet', 15 'Tech Pegs' and two 'Endurance Storm Straps' to help retain stability of your awning in poorer weather conditions.
- ◆ Lumi-Link Tube Light Kit—An excellent triple LED 12V roof light accessory, utilising six brightness settings, remote dimmers and three power options.
- ◆ Lumi-Mosquito Light—A convenient 2 in 1 LED lantern light and ultra-violet mosquito killer.
- ◆ Esprit Pro Tall Annexe—An air-framed annexe, which can be zipped to either side of the awning, offering a sleeping/storage area for up to two adults.

⇒ Visit www.outdoor-revolution.com for more information.

LIFETIME GUARANTEE

The air-frame tubes incorporate an exclusive “**LIFETIME GUARANTEE**”.

You must register for the “**LIFETIME GUARANTEE**” on the ‘Outdoor Revolution’ website **within 14 days** to validate it.

Terms and Conditions apply - find the full terms and conditions on our website!

TROUBLE SHOOTING

PROBLEM	REASON	SOLUTION
The air-tube keeps deflating after removing the pump.	The 'Dynamic Speed Valve' button hasn't been pressed back out.	Press the quick release button back out to shut the valve.
The awning is leaking.	The awning requires 'weathering' two to three times before it fully seals itself, so you may experience a little bit of weeping. This could also be condensation; an inevitable occurrence.	Allow the awning to get wet, then dry, two to three times. Open all vents to increase air-flow and reduce condensation.
Bowing and twisting of the tubes.	The tubes can twist inside the sleeves, particularly when packing away so next time the tube bows...	Un-zip the sleeve whilst the tube is deflated and re-position the tube.

IN THE EVENT OF A PUNCTURE

If you have a small puncture in your 'Oxygen Air Frame Tube', you can easily repair it using the 'Standard Puncture Repair Kit'.

- ◆ To remove the 'Air Frame Tube' - deflate the tube and then un-zip the two protective sleeves over the tube and pull the air-tube itself out. Do not unzip the sleeves whilst the tube is inflated.
- ◆ Locate and repair the puncture on the 'Air-Frame Bladder'.
- ◆ Place the air-tube back into the sleeves, in the correct place, with the valves in the 'valve hole'. Make sure the tube is straight and not twisted.
- ◆ Zip the two sleeves back up fully.
- ◆ Inflate the air frame tube again, ensuring that the puncture has now been repaired.
- ◆ If this process doesn't work; you may have to buy a new bladder!

****Spare air-frame bladders can be purchased to replace damaged ones. Visit the spares section at: www.outdoor-revolution.com, or contact us on 01924 455313****

****Awnings will not be replaced because of damaged bladders****

PACKING AWAY YOUR AWNING

- ◆ Remove any annexes and replace the door panel. Zip-up all windows and doors before deflating.
- ◆ Unpeg the guylines, storm straps and most of the pegs around the awning, leaving the four corners pegged out.
- ◆ Open each of the 'Dynamic Speed Valves' in turn and press in the quick-release button. Leave the button pressed in.
- ◆ Unpeg the four corners and pull the awning out of the awning channel.



Using the storm strap handles on the corner of the awning; lay the awning flat on the floor, with the roof folded onto the front of the awning. Push as much air out of the tube as possible.

Fold the side panels of the awning in on itself to make the awning rectangular and easier to fold up.



Next, fold the awning in on itself to make a long, thin sausage shape. Measure the width of the awning sausage against the bag to make sure it will fit into the bag. Start rolling the awning and squishing the air out as you roll.

Roll the now rolled awning onto the bag and pull the sides up around it. Finally, zip-up the bag.



PLEASE READ THE INSTRUCTIONS CAREFULLY

TIP: Refer to these photographs to assist when pitching your 'Esprit 360 Pro'.

1. Spread the flysheet out on the ground next to your caravan, with the cowl side laying parallel to your vehicle.



2. Take the awning piping and slide it through the caravan awning channel, until the awning is in the desired position on the vehicle; we recommend someone else holding the flysheet up whilst you do this.



3. Peg down the rear pads at the back of the awning against the caravan, using the adjustable pegging points. Use the strap along the floor on the inside to ensure the sides are in the correct position when doing this.



4. Locate the 'Dynamic Speed Valve' and ensure the valve is **closed**, before attaching the pump (the valve is closed when the button is pressed out).

5. Next, attach the pump to the 'Dynamic Speed Valve' and begin to carefully inflate, taking care that the fabric is not caught anywhere.



6. Inflate the air-frame until you can give it a good squeeze; the frame needs to have room inside for air to expand. Don't worry if you do keep inflating - the 'Intelligent Frame Relief Valve' will release any excess air (please note that the 'Intelligent Frame Relief Valve' is set to a limit of 5.5PSI before it will release air).

7. Replace the cap on the 'Dynamic Speed Valve' and cover the valves with the flap to prevent water getting inside.



8. Peg out and tension the front of the awning; use the adjustable pegging straps to tension the awning as you desire. Again, using the strap along the floor (on the inside) to ensure the tubes are in the correct place; make sure you don't over-tension the fabric. If a door zip is too tight, release some tension before closing - never force the zip.

9. Next, inflate the two support air-beams included and velcro these into the corresponding pads on the roof.



9. Peg out all remaining pegging points and guylines, starting from the corner against the vehicle and working your way around the awning.



10. Next, peg out all guylines and 'Endurance Storm Straps' for extra stability. Please make sure that in harsher weather, you use all of the guylines and storm straps provided to hold the awning securely in place. In very windy conditions, we recommend dropping your awning altogether.

11. Next, thread the 'Draught Skirt' through the lower awning channel and secure it at either side using 'Groundsheet Pegs'.



12. Finally, the triangular pieces can either be pegged onto the inside, to overlap the draught skirt, or on the outside—whichever you prefer!

WARNING: Never un-zip the zips on the protective sleeves whilst the air-frame tubes are inflated; this will result in the tube bursting/ballooning out of the sleeve, causing damage to the tube and the sleeve. This is not covered under the warranty!